

- 316L# SS Housing
- 3mm toughened glass diffuser
- CE/SAA/IP20/IP65/Class 1
- CREE/Bridgelux COB: 3000K/4000K/6000K/CRI≥80/90
- Beam Angle: 12°/24°/36°/60°
- Input: 220-240Vac/WT:-20~+50° C
- Warranty: 3/5 years

- **CODE - IP20** **COLOR**
 PDRASSM081520 MIRRORED
 PDRASSB081520 BRUSHED
POWER: 1x5/10W




- **CODE - IP20** **COLOR**
 PDRASSM082020 MIRRORED
 PDRASSB082020 BRUSHED
POWER: 1x5/10W

- **CODE - IP20** **COLOR**
 PDRASSM083020 MIRRORED
 PDRASSB083020 BRUSHED
POWER: 1x5/10W



- **CODE - IP65** **COLOR**
 PDRASSM081565 MIRRORED
 PDRASSB081565 BRUSHED
POWER: 1x5/10W

- **CODE - IP65** **COLOR**
 PDRASSM082065 MIRRORED
 PDRASSB082065 BRUSHED
POWER: 1x5/10W

- **CODE - IP65** **COLOR**
 PDRASSM083065 MIRRORED
 PDRASSB083065 BRUSHED
POWER: 1x5/10W



• **PHOTOMETRIC [Unit: cd]**



- **PERFORMANCE**
 1x5W - 36V - 150mA - 554lm
 1x10W - 36V - 250mA - 1112lm