

- Aluminium housing with corrosion resistant powdercoat
- 3mm toughened glass diffuser
- CE/SAA/IP20/IP65/Class 1
- CREE/Bridgelux COB: 3000K/4000K/6000K/CRI≥80/90
- Beam Angle: 12°/24°/36°/60°
- Input: 220-240Vac/WT:-20~+50° C
- Warranty: 3/5 years

- **CODE - IP20** **COLOR**
SDRBB081220 BLACK
SDRBW081220 WHITE

POWER: 1x5/10W

- **CODE - IP20** **COLOR**
SDRBB081520 BLACK
SDRBW081520 WHITE

POWER: 1x5/10W

- **CODE - IP20** **COLOR**
SDRBB082020 BLACK
SDRBW082020 WHITE

POWER: 1x5/10W

- **CODE - IP65** **COLOR**
SDRBB081265 BLACK
SDRBW081265 WHITE




POWER: 1x5/10W

- **CODE - IP65** **COLOR**
SDRBB081565 BLACK
SDRBW081565 WHITE



POWER: 1x5/10W

- **CODE - IP65** **COLOR**
SDRBB082065 BLACK
SDRBW082065 WHITE

POWER: 1x5/10W



• **PHOTOMETRIC [Unit: cd]**



• **PERFORMANCE**

- 1x5W - 36V - 150mA - 554lm
- 1x10W - 36V - 250mA - 1112lm