




- Aluminium housing with corrosion resistant powdercoat
- 3mm toughened glass diffuser
- Cut out : $\Phi 125-145\text{mm}$
- CE/SAA/IP20/IP65
- CREE/Bridgelux COB: 3000K/4000K/6000K/CRI $\geq 80/90$
- Beam Angle: 12°/24°/36°/60°
- Input: 220-240Vac/WT:-20~+50° C
- Warranty: 3/5 years

- **CODE - IP20** **COLOR**
- DLRAB15173020 BLACK
- DLRABW15173020 BLACK+WHITE
- DLRABG15173020 BLACK+GOLD
- DLRAW15173020 WHITE
- DLRAWB15173020 WHITE+BLACK
- DLRAWG15173020 WHITE+GOLD




POWER: 1x10/15/20/25W

- **CODE - IP65**
- DLRAB15173065 BLACK
- DLRABW15173065 BLACK+WHITE
- DLRABG15173065 BLACK+GOLD
- DLRAW15173065 WHITE
- DLRAWB15173065 WHITE+BLACK
- DLRAWG15173065 WHITE+GOLD

POWER: 1x10/15/20/25W



• **PHOTOMETRIC [Unit:: cd]**



• **PERFORMANCE**

- 1x10W - 36V - 250mA - 1182lm
- 1x15W - 36V - 350mA - 1743lm
- 1x20W - 36V - 500mA - 2385lm
- 1x25W - 36V - 650mA - 2756lm