




- Aluminium housing with corrosion resistant powdercoat
- 3mm toughened glass diffuser
- Cut out : $\Phi 155-170\text{mm}$
- CE/SAA/IP20/IP65
- CREE/Bridgelux COB: 3000K/4000K/6000K/CRI $\geq 80/90$
- Beam Angle: 12°/24°/36°/60°
- Input: 220-240Vac/WT:-20~+50° C
- Warranty: 3/5 years

- **CODE - IP20** **COLOR**
- DLRAB18183520 BLACK
- DLRABW18183520 BLACK+WHITE
- DLRABG18183520 BLACK+GOLD
- DLRAW18183520 WHITE
- DLRAWB18183520 WHITE+BLACK
- DLRAWG18183520 WHITE+GOLD




POWER: 1x15/20/30W

- **CODE - IP65**
- DLRAB18183565 BLACK
- DLRABW18183565 BLACK+WHITE
- DLRABG18183565 BLACK+GOLD
- DLRAW18183565 WHITE
- DLRAWB18183565 WHITE+BLACK
- DLRAWG18183565 WHITE+GOLD

POWER: 1x15/20/30W



• **PHOTOMETRIC [Unit:: cd]**



• **PERFORMANCE**

- 1x15W - 36V - 350mA - 1719lm
- 1x20W - 36V - 500mA - 2334lm
- 1x30W - 36V - 750mA - 3478lm