




- Aluminium housing with corrosion resistant powdercoat
- 3mm toughened glass diffuser
- Cut out :  $\Phi 85-95\text{mm}$
- CE/SAA/IP20/IP65
- CREE/Bridgelux COB: 3000K/4000K/6000K/CRI $\geq 80/90$
- Beam Angle: 12°/24°/36°/60°
- Input: 220-240Vac/WT:-20~+50° C
- Warranty: 3/5 years

- **CODE - IP20**      **COLOR**
- DLRAB10132220      BLACK
- DLRABW10132220      BLACK+WHITE
- DLRABG10132220      BLACK+GOLD
- DLRAW10132220      WHITE
- DLRAWB10132220      WHITE+BLACK
- DLRAWG10132220      WHITE+GOLD



POWER: 1x5/10/15W

- **CODE - IP65**
- DLRAB10132265      BLACK
- DLRABW10132265      BLACK+WHITE
- DLRABG10132265      BLACK+GOLD
- DLRAW10132265      WHITE
- DLRAWB10132265      WHITE+BLACK
- DLRAWG10132265      WHITE+GOLD

POWER: 1x5/10/15W



• **PHOTOMETRIC [Unit:: cd]**



• **PERFORMANCE**

- 1x5W - 36V - 150mA - 554lm
- 1x10W - 36V - 250mA - 1112lm
- 1x15W - 36V - 350mA - 1629lm